

4225

■ 6" HELICAL JOINTER

OLIVER

- 6" Cutting Capacity
- Oliver HCX Helical Cutterhead
- Updated to 3HP 1Ph Motor



HCX
HELICAL CUTTERHEADS
BY OLIVER

4225

6" HELICAL CUTTERHEAD JOINTER



The Oliver 4225.215 6" jointer is an excellent choice for those looking for additional cutting capacity. Our freshened up 6" Jointer includes an updated design with relocated power switch and increased horsepower.

Features

- Extra-long precision ground tables provide a stable work surface.
- Parallelogram design provides accurate cuts.
- Cast iron frame offers stable table support.
- Fully enclosed cabinet with 4" port for superior dust management.
- Built-in mobile base with lockable wheels.
- Cabinet includes push pad storage.
- Oliver HCX Helical cutterheads with premium carbide inserts.
- 4-sided cutting inserts are indexed and easy to replace.
- Lever controlled infeed and outfeed table adjustment allows quick set-up.
- Long precision ground fence tilts up to 135° with positive stops at 45° and 90°.
- Easy to read depth of cut gauge.
- Large, lockable pedestal mounted paddle on/off switch for added safety.
- Powerful TEFC 1.5HP single-phase motor.
- Poly V-belt drive.
- CSA Listed.



HCX
HELICAL CUTTERHEADS
BY OLIVER

Equipped with a true helical Oliver HCX Cutterhead.



800-559-5065 | 253-867-0334
info@olivermachinery.net
www.olivermachinery.net

4225.230 Specifications	
Model Number	4225.215
Stock Number	4235.230 (3HP, 1Ph, Helical)
Infeed Table Travel	1/2"
Cutterhead Speed	5,500 RPM
Number of Knives (helical)	36 Inserts
Maximum Depth of Cut	1/8"
Rabbeting Capacity	1/2"
Dust Port Diameter	4"
Table Dimensions	72" L x 8" W
Table Height	31-1/2"
Fence Dimensions	38" x 5"
Fence Tilts	90°, 45°, 135°
Positive Stops	90° and 45°
Motor 1Ph	1.5HP, 115V/230V, Prewired 115V (1Ph, 13/6.5 Amp)
Net Weight	352 lbs.
Gross Weight	490 lbs.



Easy assembly for power perch, simply rotate 180 degrees.



Parallelogram design for accuracy and repeatability.



Infeed table adjustment and lock.



New power switch perch for safety.